PATENT ABSTRACTS OF JAPAN

(11)Publication number:

57-091725

(43) Date of publication of application: 08.06.1982

(51)Int.Cl. -

B01D 53/36

(21)Application number : 55-169802

(71)Applicant: MATSUSHITA SEIKO CO LTD

(22) Date of filing:

01.12.1980

(72)Inventor: ITO YOSHITAKA


KANEDA YASUNORI

(54) EXHAUST-GAS TREATING DEVICE

(57) Abstract:

PURPOSE: To enhance a thermal efficiency and reduce the amount of a fuel consumed, by a method wherein a part of a high-temperature gas discharged from a catalyst bed is returned into a heating chamber.

CONSTITUTION: After a solvent-containing gas is treated by a pretreatment filter 1 to remove dusts, mists, tar and the like from the gas, it is preheated by bringing into heat exchange with a high-temperature gas from the catalyst bed 5 in a heat exchanger 3. The gas thus preheated is further heated by a burner 8 in a heating chamber, and is fed into the catalyst bed 5, where it is clarified through decomposition. Part of the exhaust gas discharged from the catalyst bed 5 at a high temperature due to the combustion of solvent components under a catalytic action is fed into the heating chamber 4 through a damper 12 provided in an exhaust-gas passage 10 for the



heating chamber 4, and it heats the solvent- containing gas directly. The remainder of the exhaust gas is fed into the heat exchanger 3 through an exhaust-gas passage 9 for the heat exchanger 9, and it preheats the solvent-containing gas.

LEGAL STATUS

[Date of request for examination]

[Date of sending the examiner's decision of rejection]

[Kind of final disposal of application other than the examiner's decision of rejection or application

converted registration]

[Date of final disposal for application]

[Patent number]

[Date of registration]

[Number of appeal against examiner's decision of rejection]

[Date of requesting appeal against examiner's decision of rejection]

[Date of extinction of right]